


Fast assembly concealed hinge

- ▶ System 8099 mounting plates - with oblong hole height adjustment
- ▶ For Sensys


Cross mounting plate with expanding sockets and special screws



- ▶ For $\varnothing 5 \times 12$ mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Oblong hole height adjustment ± 2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 025	9 075 026	9 075 027	9 075 028	1/50 ea.
37	9 071 595	9 071 596	9 071 597	9 071 598	200 ea.


Cross mounting plate with premounted Euro screws



- ▶ For $\varnothing 5 \times 12$ mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Oblong hole height adjustment ± 3 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 055	9 075 056	9 075 057	9 075 058	1/50 ea.
37	9 071 625	9 071 626	9 071 627	9 071 628	200 ea.

Patented "Hettich Direkt" cross mounting plate with locating pin and special screws



- ▶ For $\varnothing 5 \times 7.5$ mm drillings
- ▶ Quality classification under EN 15570, Level 2
- ▶ Hole spacing 32 mm
- ▶ Half overlay door, from 15 mm side panel thickness
- ▶ Oblong hole height adjustment ± 2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 015	9 075 016	9 075 017	9 075 018	1/50 ea.
37	9 071 585	9 071 586	9 071 587	9 071 588	200 ea.