

Fast assembly concealed hinge with integrated Silent System

- ▶ Sensys 8645i
- ▶ Opening angle 110°, packaging unit 200 ea.



- ▶ Concealed hinge with clip on installation and integrated Silent System
- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 24 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated +/- 2 mm overlay adjustment
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: steel, nickel plated
- ▶ Hinge cup material: steel, nickel plated

Sensys 8645i, opening angle 110°

| Cup assembly | Drilling pattern | Mounting drilling ø x T mm | full overlay | half overlay | inset | PU |
|-----------------------------|------------------|-------------------------------|-------------------|------------------|------------------|---------|
| | | | Base B 12.5 mm | Base B 3 mm | Base B -4 mm | |
| For screwing on TH 52 | | - | 9 071 205 | 9 071 206 | 9 071 207 | 200 ea. |
| For pressing in TH 53 | | ø 10 x 11 | 9 071 208 | 9 071 209 | 9 071 210 | 200 ea. |
| Fix fast assembly THS 55 | | ø 10 x 6 | 9 071 220 | 9 071 221 | 9 071 222 | 200 ea. |
| For screwing on TB 52 | | - | 9 071 223 | 9 071 224 | 9 071 225 | 200 ea. |
| For pressing in TB 53 | | ø 8 x 11 | 9 071 226 | 9 071 227 | 9 071 228 | 200 ea. |
| Fix fast assembly TB 55 | | ø 8 x 6 | 9 071 238 | 9 071 239 | 9 071 240 | 200 ea. |