


- System 8099 mounting plates – with oblong hole height adjustment
- For Sensys


Cross mounting plate for screwing on



- For 4.5 mm $\varnothing$ x 16 mm countersunk screws
- Quality classification under EN 15570, Level 3
- Hole spacing 32 mm
- Oblong hole height adjustment ± 3 mm
- Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 005	9 075 006	9 075 007	9 075 008	1/50 ea.
37	9 071 575	9 071 576	9 071 577	9 071 578	200 ea.


Cross mounting plate for pressing in



- For $\varnothing 10 \times 12$ mm drillings
- Quality classification under EN 15570, Level 3
- Hole spacing 32 mm
- Oblong hole height adjustment ± 2 mm
- Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 045	9 075 046	9 075 047	9 075 048	1/50 ea.
37	9 071 615	9 071 616	9 071 617	9 071 618	200 ea.

Cross mounting plate with expanding sockets and special screws



- For $\varnothing 10 \times 12$ mm drillings
- Quality classification under EN 15570, Level 3
- Hole spacing 32 mm
- Oblong hole height adjustment ± 2 mm
- Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 035	9 075 036	9 075 037	9 075 038	1/50 ea.
37	9 071 605	9 071 606	9 071 607	9 071 608	200 ea.