

Fast assembly concealed hinge with integrated Silent System

► Sensys 8639i W90

► For 90° face angle applications, opening angle 95°



- Concealed hinge with clip on installation and integrated Silent System
- Quality classification under EN 15570, Level 3
- For corner cabinets
- For door thickness 15 - 28 mm
- Cup diameter 35 mm
- Cup depth 12.8 mm
- Integrated adjustment of door offset + 1 mm / - 2 mm
- Integrated reveal adjustment + 3 mm / - 2 mm
- Height adjustment at mounting plate
- Hinge arm material: zinc die-cast nickel plated
- Hinge cup material: steel nickel plated

Sensys 8639i W90, opening angle 95°

inset



Cup assembly	Drilling pattern	Mounting drilling ø x T mm	Base B 4 mm	PU
For screwing on TH 52		-	9 088 021	1/50 ea.
For pressing in TH 53		ø 10 x 11	9 088 039	1/50 ea.
Flash fast assembly TH 54		ø 10 x 11	9 088 057	1/50 ea.
Fix fast assembly THS 55		ø 10 x 6	9 088 075	1/50 ea.
For screwing on TB 52		-	9 088 027	1/50 ea.
For pressing in TB 53		ø 8 x 11	9 088 045	1/50 ea.
Flash fast assembly TB 54		ø 8 x 11	9 088 063	1/50 ea.
Fix fast assembly TB 55		ø 8 x 6	9 088 081	1/50 ea.